

Crimping Pliers

8155 CRIMP WRENCH


for insulated connector

- > For red, blue and yellow insulated connectors, such as cable terminals, pin cable terminals, flat plugs, flat sockets, round plugs, round sockets, push connectors and parallel connectors
- > Easy to handle
- > Releasable positive locking
- > Kind-to-hands formed handles
- > GEDORE special steel, gun-metal finish

Field of application:

- > 1: 0.5-1.0 mm² / 20-18 AWG
- > 2: 1.5-2.5 mm² / 16-14 AWG
- > 3: 4.0-6.0 mm² / 12-10 AWG



mm ²	AWG	L	W		Code	No.
0,5-6	20-10	220	80	0.480	2836823	8155

8156 CRIMP WRENCH


for non-insulated contacts

- > For non-insulated contacts with open crimping sleeve, such as flat plugs F 2.8; F4.8; F6.3 and F 9.5
- > Easy to handle
- > Releasable positive locking
- > Kind-to-hands formed handles
- > GEDORE special steel, gun-metal finish

Field of application:

- > 1: 0.25-0.5 mm² / 24-20 AWG
- > 2: 0.5-1.0 mm² / 20-18 AWG
- > 3: 4.0-6.0 mm² / 12-10 AWG
- > 4: 1.5-2.5 mm² / 16-14 AWG



mm ²	AWG	L	W		Code	No.
0,25-6	24-10	220	80	0.510	2836831	8156

8157 CRIMP WRENCH


for cable lugs

- > For non-insulated contacts with closed crimping sleeve (W pressing) up to 16 mm² / AWG 6 and tubular cable lugs up to 10 mm² / AWG 6
- > Easy to handle
- > Releasable positive locking
- > Kind-to-hands formed handles
- > GEDORE special steel, gun-metal finish

Field of application:

- > 1: 0.1-0.35 mm² / 26-22 AWG
- > 2: 0.5-1.0 mm² / 20-18 AWG
- > 3: 1.5-2.5 mm² / 16-14 AWG
- > 4: 4.0-6.0 mm² / 12-10 AWG
- > 5: 10.0-16.00 mm² / 8-6 AWG



mm ²	AWG	L	W		Code	No.
0,1-16	26-6	220	80	0.470	2836858	8157