

Water Pump / Universal Pliers

142 UNIVERSAL PLIERS

- > Acc. to DIN ISO 8976 Form C
- > With safety box joint and protection against blocking
- > Fine adjustment
- > 142 7 = 17 settings
- > 142 10 = 15 settings
- > 142 12 = 17 settings

- > Single-hand push-button adjustment
- > Slender pliers head for places that are hard to access
- > Long slim jaws
- > Offset gripping faces for self-gripping of nuts and pipes
- > GEDORE special chrome-vanadium steel
- > Induction-rehardened serrated faces

- > Model C = slim handles with forged serrations
- > Model TL = steel-grey, with blue dipped handle protectors
- > Model JC = chrome-plated, with 2-component handles




142 10 JC



142 10 C



142 10 TL



L ₁	L ₂	b	h			Code	No.
180	32	6.5	40	37	0.183	2668211	142 7 TL
180	32	6.5	40	37	0.173	2668238	142 7 C
255	39	7.5	48	38	0.371	6416180	142 10 TL
250	39	7.5	48	38	0.380	6416260	142 10 C

L ₁	L ₂	b	h			Code	No.
260	39	7.5	48	38	0.417	6416340	142 10 JC
309	43	8.5	55	44	0.550	1995413	142 12 TL
300	43	8.5	55	44	0.530	1995553	142 12 C

143 UNIVERSAL PLIERS

6 settings


- > Acc. to DIN ISO 8976 Form B
- > Slim head
- > Forged twin-groove lay-on slip joint and toothed recess
- > Offset gripping faces for self-gripping of nuts and pipes
- > With finger protection
- > For pipes up to 1.1/2" and nuts up to 38 mm
- > GEDORE special chrome-vanadium steel, chrome-plated
- > Induction-rehardened serrated faces
- > Model C = slim handles with forged serrations
- > Model JC = chrome-plated, with 2-component handles



143 10 JC



143 10 C



L ₁	L ₂	b	h			Code	No.
256	40	10.6	56	38	0.340	6410650	143 10 C
262	40	10.6	56	38	0.390	6415880	143 10 JC

144 MECHANICS PLIERS

7 settings


- > Acc. to DIN ISO 8976 Form A
- > Lay-on slip joint and straight, serrated jaws
- > GEDORE special chrome-vanadium steel
- > Induction-rehardened serrated faces



144 1/2 C



144 7 C



L ₁	L ₂	b	h			Code	No.
113	13	3.8	23	16	0.042	6411110	144 4.1/2 C
175	22	5.5	35	26	0.138	6411380	144 7 C