


145 WATER PUMP PLIERS

- > Acc. to DIN ISO 8976 Form A
- > Lay-on slip joint and toothed recess
- > Induction-rehardened serrated faces, with finger protection
- > Clamps automatically on pipes and nuts
- > GEDORE special chrome-vanadium steel, chrome-plated
- > Model C = handles cross-hatched
- > Model JC = with 2-component handles
- > 145 10 = 7 settings, with extra narrow jaws
- > 145 15 = 9 settings
- > 145 20 = 11 settings




L ₁	L ₂	b	h			Code	No.
250	41	7.8	47	39	0.365	6412000	145 10 C
260	41	7.8	47	39	0.425	6415610	145 10 JC
375	46	10.4	72	50	0.854	6412190	145 15 C
500	55	13.8	98	65	1.747	6412270	145 20 C

146 UNIVERSAL PLIERS

7 settings

- > Acc. to DIN ISO 8976 Form C
- > With safety box joint and finger protection
- > Automatic clamping with offset gripping surfaces
- > GEDORE special chrome-vanadium steel, chrome-plated, with polished surface
- > Induction-rehardened serrated faces
- > Model C = slim handles with forged serrations
- > Model JC = chrome-plated, with 2-component handles



L ₁	L ₂	b	h			Code	No.
250	32.5	4.8	48	31	0.335	6413240	146 10 C
250	32.5	4.8	48	31	0.400	2672626	146 10 JC

146 B SPECIAL WATER PUMP PLIERS

5 settings

- > Acc. to DIN ISO 8976 Form C
- > With fast adjustment and tooth-lock box joint and toothed aperture
- > Absolutely safe - no slipping out of adjustment during work
- > With finger protection
- > GEDORE special chrome-vanadium steel, chrome-plated, polished



L ₁	L ₂	b	h			Code	No.
250	45	8	55	50	0.485	6412510	146 B 10

9144 WATER PUMP PLIERS

- > Acc. to DIN ISO 8976
- > Chrome-vanadium steel
- > With box joint
- > Drop forged



L ₁	L ₂	b	h			Code	No.
175	28	7.0	33	26	0.150	4533230	914417
240	35	7.5	40	33	0.290	4533310	914424
300	40	9.0	60	45	0.480	4533580	914430