

VDE 1993 U

VDE REVERSIBLE RATCHET 1/2"



with push-button release

- > Robust, with smooth action
- > Sockets held absolutely securely by push-button lock with ball in the square drive
- > Direction changed by 2 push-buttons, marked R and L, on the shaft
- > Return angle 10 degrees
- > Square drive acc. to DIN 3120 - A 12.5, ISO 1174, chrome-vanadium steel 31CrV3
- > VDE insulation up to 1000 V, acc. to EN 60900/IEC 60900



"	mm	mm	kg	Code	No.
1/2	12.5	270	0.546	6123910	VDE 1993 U


V 42

VDE HEXAGON ALLEN KEY

for in-hex screws

△ 1000 V

- > Acc. to DIN ISO 2936
- > Particularly suitable for cable branch clamping rings
- > Oil-hardened
- > GEDORE vanadium special steel
- > Individually tested, insulation up to 1000 V



mm	L ₁	L ₂	kg	Code	No.
3	130	23.5	0.020	2324849	V 42 3
4	120	40.0	0.025	2324857	V 42 4
5	140	48.0	0.045	2324865	V 42 5
6	140	48.0	0.060	2324873	V 42 6
8	150	51.0	0.110	2324881	V 42 8
10	220	51.0	0.230	2324903	V 42 10
12	260	61.5	0.350	2324911	V 42 12

V 42 T

VDE HEXAGON ALLEN KEY WITH T-HANDLE

△ 1000 V

for in-hex screws

- > Individually tested, insulation up to 1000 V
- > With Check-Tool insulation
- > GEDORE chrome-vanadium steel 59CrV4



mm	mm	X	kg	Code	No.
4	160	X	0.145	2661225	V 42 T 4
5	160	X	0.250	2661233	V 42 T 5
6	160	X	0.250	2661241	V 42 T 6
8	160	X	0.260	2661268	V 42 T 8
10	200	-	0.390	2661276	V 42 T 10
11	200	-	0.400	2661284	V 42 T 11
12	200	-	0.420	2661292	V 42 T 12

VDE 2170

VDE SCREWDRIVER

△ 1000 V

for slotted head screws

- > Individually tested, VDE insulation up to 1000 V, acc. to EN 60900/IEC 60900, fully insulated blade
- > Tip to DIN ISO 2380-1 form B
- > 3-component handles Power-Grip³ with hanging hole
- > Ergonomic handle design enables precise and fatigue-free working
- > Positive-fit joint of handle and blade for optimum transmission of force
- > Type of drive marked at end of the handle
- > Blade from GEDORE molybdenum-vanadium-Plus tempered steel



mm	mm	mm	mm	kg	Code	No.
2.5	0.4	75	160	0.038	1612220	VDE 2170 2,5
3.0	0.5	100	185	0.042	1612239	VDE 2170 3
3.5	0.6	100	185	0.055	1612247	VDE 2170 3,5
4.0	0.8	100	185	0.058	1612255	VDE 2170 4
5.5	1.0	125	225	0.095	1612271	VDE 2170 5,5
6.5	1.2	150	260	0.134	1612298	VDE 2170 6,5
8.0	1.2	175	295	0.158	1612301	VDE 2170 8
10.0	1.6	200	320	0.208	1612336	VDE 2170 10