


## SLIM DRIVE

No problems in reaching screws deeply embedded in screw shafts

- Ultra-small blade diameter yet with full mechanical and electrical safety
- No problems in reaching screws deeply embedded in screw shafts
- VDE insulation up to 1000 V, acc. to EN 60900/IEC 60900, fully insulated blade
- 3-component handles Power-Grip<sup>3</sup> with hanging hole
- Ergonomic handle design enables precise and fatigue-free working
- Positive-fit joint of handle and blade for optimum transmission of force
- Type of drive marked at end of the handle
- Blade from GEDORE molybdenum-vanadium-Plus tempered steel



## VDE 2172 VDE SCREWDRIVER SLIM DRIVE

for slotted head screws

- Individually tested, VDE insulation up to 1000 V, acc. to EN 60900/IEC 60900, fully insulated blade
- 3-component handles Power-Grip<sup>3</sup> with hanging hole
- Ergonomic handle design enables precise and fatigue-free working
- Positive-fit joint of handle and blade for optimum transmission of force
- Type of drive marked at end of the handle
- Ultra-small blade diameter yet with full mechanical and electrical safety
- No problems in reaching screws deeply embedded in screw shafts
- Blade from GEDORE molybdenum-vanadium-Plus tempered steel



▲ 1000 V

## V 2160 MS PH SCREWDRIVER MAVO

for cross-head screws PH

- No-contact voltage finder and fitted magnetic field tester
- Voltage fields are displayed in red and magnetic fields in green
- The no-contact voltage finder detects energised conductors. The capacitive testing method can localise a break in the cable down to a few millimeters.
- The magnetic field tester examines the function of electro-magnetic switches and valves without having to place the switch out of service. Both permanent and alternating magnetic fields are displayed
- 3-component handles Power-Grip<sup>3</sup>
- Ergonomic handle design enables precise and fatigue-free working
- Positive-fit joint of handle and blade for optimum transmission of force
- Blade from GEDORE molybdenum-vanadium-Plus tempered steel
- Individually tested, insulation up to 1000 V

▲ 1000 V



winner

$\oplus$ mm	$\ominus$ mm	$\frac{1}{4}$ mm	$\frac{5}{16}$ mm	$\frac{3}{8}$ kg	Code	No.
3.5	0.6	100	185	0.055	2824736	VDE 2172 3,5
4.0	0.8	100	185	0.055	2824744	VDE 2172 4
5.5	1.0	125	225	0.100	2824752	VDE 2172 5,5
6.5	1.2	150	260	0.140	2824760	VDE 2172 6,5



$\oplus$ PH	$\ominus$ M	$\frac{1}{4}$ mm	$\frac{5}{16}$ mm	$\frac{3}{8}$ kg	Code	No.
2	M3,5 - M5	100	210	0.140	2824434	V 2160 MS PH 2

## VDE 2160 PH VDE SCREWDRIVER

for cross-head screws PH

- Individually tested, VDE insulation up to 1000 V, acc. to EN 60900/IEC 60900, fully insulated blade
- Blade tip to DIN ISO 8764-1 PH
- 3-component handles Power-Grip<sup>3</sup> with hanging hole
- Ergonomic handle design enables precise and fatigue-free working
- Positive-fit joint of handle and blade for optimum transmission of force
- Type of drive marked at end of the handle
- Blade from GEDORE molybdenum-vanadium-Plus tempered steel



▲ 1000 V

## VDE 2160 PZ VDE SCREWDRIVER

for cross-head screws Pozi PZ

- Individually tested, VDE insulation up to 1000 V, acc. to EN 60900/IEC 60900, fully insulated blade
- Blade tip to DIN ISO 8764-1 PZ
- 3-component handles Power-Grip<sup>3</sup> with hanging hole
- Ergonomic handle design enables precise and fatigue-free working
- Positive-fit joint of handle and blade for optimum transmission of force
- Type of drive marked at end of the handle
- Blade from GEDORE molybdenum-vanadium-Plus tempered steel

▲ 1000 V



$\oplus$ PH	$\ominus$ M	$\frac{1}{4}$ mm	$\frac{5}{16}$ mm	$\frac{3}{8}$ kg	Code	No.
0	M1,6 - M2	60	145	0.039	1612107	VDE 2160 PH 0
1	M2 - M3	80	180	0.082	1612115	VDE 2160 PH 1
2	M3,5 - M5	100	210	0.119	1612123	VDE 2160 PH 2
3	M5,5 - M7	150	270	0.188	1612131	VDE 2160 PH 3
4	M8 - M10	200	320	0.269	1612158	VDE 2160 PH 4

$\oplus$ PZ	$\ominus$ M	$\frac{1}{4}$ mm	$\frac{5}{16}$ mm	$\frac{3}{8}$ kg	Code	No.
0	M1,6 - M2	60	145	0.038	1612166	VDE 2160 PZ 0
1	M2 - M3	80	180	0.082	1612182	VDE 2160 PZ 1
2	M3,5 - M5	100	210	0.120	1612190	VDE 2160 PZ 2
3	M5,5 - M7	150	270	0.188	1612204	VDE 2160 PZ 3
4	M8 - M10	200	320	0.270	1612212	VDE 2160 PZ 4